

DECLARATION OF PERFORMANCE

No.10-12057-16052014

1. Unique identification of the product type: **Offerdal Quartzite, Natural stone product, Modular tiles**
2. Type-, batch or serial number or any other element allowing identification of the construction product as required in Article 11(4) of the CPR : **Packaging and packing list are marked and can be identified in the documented Factory production control (FPC).**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specifications as foreseen by the manufacturer : **Modular tiles of natural stone which are made for use as flooring, stairs, cladding and ceiling finishes.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required in Article 11(5) : **Minera Skiffer AB, Odenskogsvägen 1, 83148 Östersund, Sweden**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the specifications in Article 12(2) : **Not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V : **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard : **EN 12057 :2004**
8. Declared performance

| Essential characteristics | Performance | | Standard | |
|--|---|-----|-----------|-----|
| Reaction to fire | Class A1 | | 96/603/EC | |
| Water Absorption (weight%) | 0,1 | | EN 13755 | |
| Flexural strength (MPa) (CBI 2014) | Lower expected value: 25,0 Middle value: 41,8 Standard deviation: 7,9 | | EN 12372 | |
| Frost Resistance (SINTEF 2007) | Flexural strength reference: 35,1 MPa Flexural strength after cycling (48): 37,4 MPa Flexural strength, change: +1% | | EN 12371 | |
| Resistance to ageing by thermal shock (SINTEF 2007) | Weight loss (%): 0,05 Reduction in sound velocity: 11 % Visual inspection: no change | | EN 14066 | |
| Slip Resistance, SRV-value | Wet | Dry | EN 14231 | |
| | Natural cleft | NPD | | NPD |
| | Honed (C600) | 19 | | 58 |
| Apparent Density (kg/m ³) | 2750 | | EN 1936 | |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Per Göran Petterson, CEO

Östersund, ... 140528
Date and place of issue

.....
Signed