

DECLARATION OF PERFORMANCE

No. 70-12058-16052014


1. Unique identification of the product type: **Otta Phyllite, Natural stone product, slabs for floors and stairs.**
2. Type-, batch or serial number or any other element allowing identification of the construction product as required in Article 11(4) of the CPR : **Packaging and packing list are marked and can be identified in the documented Factory production control (FPC).**
3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specifications as foreseen by the manufacturer : **Natural stone slabs fabricated for use as floor and stair coverings.**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required in Article 11(5) : **Minera Skifer AS, Engan, 7340 Oppdal, Norway**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the specifications in Article 12(2) : **Not relevant**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V : **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard : **EN 12058:2008**
8. Declared performance

| Essential characteristics | Performance | Standard |
|--|--|----------|
| Water Absorption (weight%) | 0,2 | EN 13755 |
| Flexural strength (MPa) (CBI 2014) | Lowest value: 32,7 Middle value: 54,1 Standard deviation: 11,7 | EN 12372 |
| Frost Resistance, including flexural strength (CBI 2014) | Ultras. Pulse Vel. change - 5,8% Mass, change: -0,19 % Flex. strength, ref.: 54,1 MPa Flex. str. aft. cycling: 43,8 MPa | EN 12371 |
| Resistance to ageing by thermal shock (SINTEF 2007) | Weight loss (%) 0,3, Reduction in sound velocity 30 % | EN 14066 |
| Slip Resistance, Natural cleft, SRV | Wet Dry NPD NPD | EN 14321 |
| Slip Resistance Brushed | 22 61 | EN 14321 |
| Slip Resistance, Honed | 18 55 | EN 14321 |
| Apparent Density (kg/m ³) | 2820 | EN 1936 |

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by:

Arnstein Sæteren, Managing Director

Oppdal, 19/5-2014


.....